

FLUKE®


Fluke TiR Series Buildings Thermal Imagers



TiR32 shown with optional wide angle lens

The ultimate tools for energy audits, building maintenance, restoration and remediation.

Rugged, reliable, easy to use... what you expect from the worldwide leader in test and measurement tools—Fluke.



Where can thermal imaging save me time and money?



Why thermal imaging?

Productivity

Scan large areas quickly to detect problems or the extent of any damage. Whether you own your own business or maintain a commercial or residential facility, time is on your side when you use thermal imaging to get your work done.

Profitability


Turn to thermal imaging to drive improvements to your bottom line. Building inspections go much faster, saving you time and money—getting you to your next job faster. Use it to reduce energy usage or help keep mission critical equipment running.

Safety


Thermal imaging is a non-contact technology and can identify potential problems from a safe distance. Scan elevated or hard to reach surfaces without risking you or your employees' safety.

- Reduce energy usage:
 - Locate air leakage resulting from improperly installed or worn seals on windows and doors
 - Verify missing, damaged or incorrectly installed insulation
- Detect moisture intrusion and the possible existence of mold or mildew
- Extend the life of roofs by locating and fixing leaks
- Locate damaged or unsealed components of HVAC/R systems (air conditioning, heating, air handlers, and refrigeration)


Visit www.fluke.eu/ti for a library of thermal imaging case studies and application notes.




Insulation failures: Discover problems with insulation that result in elevated energy bills.



Moisture detection: Easily detect the extent of moisture damage behind interior walls, in ceilings and under carpets.



Air leakage: Identify sources of energy loss due to improperly installed or worn seals on windows and doors.



Roofing: Detect water-saturated insulation in flat-roof systems to locate damaged portions of roofing structure.

Fluke TiR Series Building Diagnostic Thermal Imagers

FLUKE®

Superior image quality

Just pick up a Fluke imager and you'll immediately see the difference. Fluke delivers the clear, crisp images needed to find and fix problems fast.

- Industry leading thermal sensitivity (NETD) enables you to identify the small temperature differences that could indicate big problems
- Even the smallest details become visible with the large, widescreen full VGA color LCD display
- Patented IR-Fusion®, only from Fluke, delivers the industry's best visible/infrared image alignment and focusing

Easy to use

When you pick up a tool, you need it to operate and deliver results without having to read a heavy manual.

- Intuitive, three-button menu is easy to use... simply navigate with the push of a thumb
- Easy, manual focus allows for precise image viewing control
- File management is effortless with the Fluke proprietary .is2 file format, which automatically stores the visual image, infrared image, voice and text annotations in one simple file (other file formats are also supported both on imager and in SmartView software)

Rugged

Tools are meant to be used, and Fluke thermal imagers are designed to reliably operate in the toughest environments.

- Engineered and tested to withstand a 2 meter drop—when was the last time you dropped a tool?
- Withstands dust and water, tested to an IP54 rating
- Use in ambient temperatures as low as -10 °C and high as +50 °C



Fluke thermal imagers are built tough to withstand long hours in the field so users can move from job-to-job quickly.



Field replaceable batteries and optional visor on the TiR32 gives you maximum flexibility no matter where your work takes you.



Award winning performance – what you've come to expect from Fluke.



Fluke TiR1


Quick Product Selection Guide

	TiR32	TiR1	TiR	TiRx
Detector type	320 x 240	160 x 120	160 x 120	160 x 120
Thermal sensitivity	50 mK	70 mK	100 mK	100 mK
Temperature range	150°C	100°C	100°C	100°C
IR-Fusion®	•	•	•	
Dew point temperature alarm	•			
Optional lenses	•			
Voice annotation	•	•		
Replaceable batteries	•			
Choice of palettes	15	6	6	4


For detailed specifications see page 7.




IR-Fusion® samples



Full (traditional) infrared: Displays a full screen infrared view for maximum infrared detail.



Picture-in-picture: Maintains a frame of reference by placing an IR "window" within a visual (visible light) image.



Blending: Blends the visible and infrared images together in any user-selected proportion to create a more compelling, understandable image.



IR/color alarm: Isolates problematic areas by displaying a visual image with infrared highlights for surface temperatures in between, above or below, or outside a user-selected range.



Full Visual (visible light): Displays a digital photographic image, as you would get from a digital camera.

More than picture in picture

Infrared images alone can be difficult to understand, which is why Fluke pioneered IR-Fusion, a revolutionary marriage of visible and infrared images never before seen in commercial or industrial thermal imagers. Automatically capturing a visible image with every infrared image allows you to you always know exactly what you're looking at.

Not all fusion is created equal

Don't be fooled by imitators. Patented IR-Fusion is the only solution with physical parallax correction, enabling the perfect alignment and blending of both infrared and visible images. While many manufacturers have attempted to duplicate Fluke IR-Fusion, none have been able to match it. Turn to Fluke IR-Fusion to deliver the industry's best thermal images.

Thermal imager features



SmartView® Software

Powerful

Everything you need for analysis and reporting.

- Extensive annotation, editing, and viewing options with full IR-Fusion® capabilities
- 3D-IR™ delivers unique three-dimensional analysis capabilities
- Multiple reporting options and templates

Easy to use


It's never been easier to enhance and analyze your thermal images.

- SmartView tools and controls allow easy access to editing functions
- Report Wizard guides you through automatic, professional report generation


Included with every imager

Fluke includes SmartView software with unlimited licenses and lifetime upgrades with every thermal imager.

- No need to pay extra for a professional software solution




Navigate, analyze and enhance IR images.



Organize data with extensive annotations.



Simplified professional report generation.



SmartView® system requirements

Software requirements

- Microsoft Windows XP/Vista
- Web browser for product registration and viewing FAQs: Microsoft® Internet Explorer 5.0 or newer
- Microsoft® Word 2007 for report template modification (optional)

Hardware requirements

- Memory card reader to transfer images to computer (included)
- 512 MB RAM (1GB for Vista), not including the space requirements for web browser and Microsoft® Word
- 16-bit color, 1024x768 resolution video or better
- Color printer for printing images (optional)
- CD-ROM drive for installing SmartView software

Thermal imaging terminology explained



Palette—Color representation of the temperatures (temperature scale) in a displayed image. Certain color palettes meet personal preferences or optimize the image for different applications and/or problems. An example of the different palettes appear to the right.


Sensor Size—Similar to digital cameras the sensor size describes the amount of displayed points per image of a thermal imager. A sensor size of 320 x 240 captures and displays more than 76,800 measurement points with each measurement. If the imager is fully radiometric then it also truly measures and stores all captured points with the image.

Field of view (FOV)—Indicates what the thermal imager sees or measures at a given moment. The combination of the Field of View specification and the distance to the measured object determines which surface or part of an object will be measured as a total. A FOV calculator on www.fluke.eu/ti helps you calculate the measurement surface at various distances to the object.


Thermal sensitivity—Indicates what the smallest temperature difference is which can be measured/displayed in an image. It basically is the maximum resolution of the image and is referred to as NETD (noise equivalent temperature difference).

Emissivity adjustment—All surfaces emit infrared energy or heat. The level of emission varies much per surface and is described with the term emissivity. Painted coatings and materials usually have a high emissivity while polished aluminum has a low emissivity. Visit www.fluke.eu/ti for a table with emissivities for different materials. To measure the temperature of a material accurately it will be necessary to adjust for the material's emissivity.


Span—The set of temperature values that can be measured within a preset range. Adjusting the span allows you to see more subtle temperature gradients (or contrast) in a captured image. When the span is optimized the imager shows 256 different shades of color in an image.



Ironbow



Blue-red



High contrast



Amber



Hot metal



Grey

Specifications

	TIR32	TIR1	TIR	TIRx
Temperature				
Temperature measurement range (not calibrated below -10 °C)	-20 °C to +150°C		-20 °C to +100 °C	
Temperature measurement accuracy	± 2 °C or 2 % (at 25°C nominal, whichever is greater)		± 5 °C or 5 % (at 25°C nominal, whichever is greater)	
On-screen emissivity correction	Yes		—	
On-screen reflected background temperature compensation	Yes		—	
On-screen transmission correction	Yes		—	
Imaging performance				
Detector type	320 X 240 Focal Plane Array, uncooled microbolometer		160 X 120 Focal Plane Array, uncooled microbolometer	
Thermal sensitivity (NETD)	≤ 0.05 °C at 30 °C (50 mK)		≤ 0.07 °C at 30 °C (70 mK)	≤ 0.1 °C at 30 °C (100 mK)
Infrared spectral band	7.5 μm to 14 μm (long wave)			
Visual (visible light) camera	Industrial Performance 2.0 Megapixel		Industrial Performance 1.3 MegaPixel	
Minimum focus distance	46 cm		—	
Standard infrared lens type				
Field of view	23 ° x 17 °			
Spatial resolution (IFOV)	1.25 mRad		2.5 mRad	
Minimum focus distance	15 cm			
Optional telephoto infrared lens type				
Field of view	11.5 ° x 8.7 °		—	
Spatial resolution (IFOV)	0.63 mRad		—	
Minimum focus distance	45 cm		—	
Optional wide-angle infrared lens type				
Field of view	46 ° x 34 °		—	
Spatial resolution (IFOV)	2.50 mRad		—	
Minimum focus distance	7.5 cm		—	
Focus mechanism	Manual, one-handed Smart Focus capability			
Image presentation				
Palettes				
Standard	Ironbow, Blue-Red, High Contrast, Amber, Amber Inverted, Hot Metal, Grayscale, Grayscale Inverted		Ironbow, Blue-Red, High Contrast, Amber, Hot Metal, Grey	Ironbow, Blue-Red, High Contrast, Grey
Ultra Contrast	Yes		—	
Level and span	Smooth auto-scaling and manual scaling of level and span			
Fast auto toggle between manual and auto modes	Yes		—	
Fast auto-rescale in manual mode	Yes		—	
Minimum span (in manual mode)	2 °C		2,5 °C	
Minimum span (in auto mode)	3 °C		5 °C	
IR Fusion® information				
Automatically aligned (parallax correctable) visual and IR blending	Yes			—
Picture-In-Picture (PIP)	Three levels of on-screen IR blending displayed in center of LCD		100 % IR displayed in center or LCD	
Full screen infrared	Three levels of on-screen IR blending displayed in center of LCD		100 % IR displayed in center of LCD	
Color alarms (temperature alarms)	Dew point temperature alarm (User selectable)		—	
Voice Annotation				
Voice annotation	60 seconds maximum recording time per image; reviewable playback on imager		—	
Image capture and data storage				
Image capture, review, save mechanism	One-handed image capture, review, and save capability			
Storage medium	SD Memory Card (2 GB memory card will store at least 1200 fully radiometric (.is2) IR and linked visual images each with 60 seconds voice annotations, or 3000 basic bitmap (.bmp) images, or 3000 jpeg (.jpeg) images; transferrable to PC via included multi-format USB card reader)			
File formats	Non-radiometric (.bmp) or (.jpeg) or fully-radiometric (.is2)		Non-radiometric (.bmp) or fully-radiometric (.is2)	
	No analysis software required for non-radiometric (.bmp and .jpeg) files		No analysis software required for non-radiometric (.bmp) files	
Export file formats w/ SmartView® software	JPEG, JPG, JPE, JFIF, BMP, GIF, DIB, PNG, TIF, and TIFF			
Memory review	Thumbnail view navigation and review selection		Sequential image navigation and review	
Software controls and adjustments				
Language selection	English, German, French, Spanish, Portuguese, Italian, Swedish, Finnish, Russian, Czech, Polish, Turkish, Simplified Chinese, Traditional Chinese, Korean, Japanese			
Image controls	Smooth auto scaling and manual scaling			
Power				
Battery type	Two replaceable rechargeable battery packs (Lithium ion)		Internal rechargeable battery NiMh (included)	
Battery operating time	4+ hours per battery pack		3 to 4 hours continuous operation	
Battery charging	Two-bay AC battery charger		2 hours with ac charger or dc car charger (charges battery while operating)	
AC operation	AC adapter/charger 110/230 V ac, 50/60Hz			
Power saving	Automatic shutdown and sleep modes (user specified)			
Environmental and mechanical design				
Operating temperature	-10 to +50 °C			
Storage temperature	-20 to +50 °C			
Relative humidity	10% to 95%, non-condensing			
Water and dust resistant	IP54			
Two meter drop test	Yes with standard lens		Yes	
Protective lens cover	Yes			
Weight (including battery)	1.05 kg		1.2 kg	
Imager size (HxWxD)	277 x 122 x 170 mm		267 x 127 x 152 mm	
Other				
Warranty	2 years			
EN 61010-1 2nd edition and EN61326-1	Yes			

Thermal imaging accessories



Everything you need to get started is included:

- In-box training DVD
 - SmartView® analysis and reporting software
 - 2 GB SD Memory Card
 - Multi-function Memory Card Reader for downloading images into your computer
 - Rugged, hard carry case and portable, soft carry case
 - Hand strap, adjustable for left of right handed user
 - Rechargeable battery (TiR32 includes two external smart rechargeable batteries)
 - AC charger/power supply
- Note: Included accessories vary by model.

Ordering information

Fluke TiR32 Thermal Imager
 Fluke TiR1 Thermal Imager
 Fluke TiR Thermal Imager
 Fluke TiRx Inspector Thermal Imager

Expand your thermal imaging capabilities with the following Fluke accessories:



FLK-LENS/TELE1
Telephoto Infrared Lens
(TiR32 only)



FLK-LENS/WIDE1 Wide-angle Infrared Lens
(TiR32 only)



TI-CAR-CHARGER
Thermal Imager Vehicle
Charger




TI-VISOR Thermal Imager
Visor



FLK-TI-SBP3
Extra battery (TiR32 only)



FLK-TI-SBC3 Charging
Base (TiR32 only)



Available
late 2009



Fluke. Keeping your world up and running.™

Fluke Corporation
 P.O. Box 9090
 Everett, WA USA 98206
Web: www.fluke.com

Fluke Europe B.V.
 P.O. Box 1186
 5602 BD Eindhoven
 The Netherlands
Web: www.fluke.eu/ti

For more information call:
 In the U.S.A. (800) 443-5853
 or Fax (425) 446-5116
 In Europe/M-East/Africa +31 (0)40 2 675 200
 or Fax +31 (0)40 2 675 222
 In Canada (905) 890-7600
 or Fax (905) 890-6866
 From other countries +1 (425) 446-5500
 or Fax +1 (425) 446-5116

Fluke (UK) Ltd.
 52 Hurricane Way
 Norwich
 Norfolk
 NR6 6JB
 United Kingdom

Tel.: (020) 7942 0700
 Fax: (020) 7942 0701
 E-mail: industrial@uk.fluke.nl
Web: www.fluke.co.uk/ti