

ELECTRONIC-TWEEZERS

| No. | Length | | Finish | Weight |
|--|--------|--------|--|--------|
| | mm | inches | | |
| Engineer's tweezers made from steel, with fine, bent tips, finely serrated | | | | |
| 5-107 | 150 | 6" | nickel-plated | 20g |
| 5-107-1 | 150 | 6" | polished, with antiallergical coating | 23 g |
| 5-107-6 | 150 | 6" | nickel-plated, strong PVC-insulated | 27 g |
| 5-107 VDE | 150 | 6" | with VDE insulation, 1000V | 37 g |
| 5-107-9 | 150 | 6" | teflon-coated | 22 g |



| | | | | |
|---|-----|--------|--|------|
| Engineer's tweezers made from steel, heavy type, straight, flat and wide, tips with serration | | | | |
| 5-117 | 145 | 5 3/4" | nickel-plated | 25 g |
| 5-117-1 | 145 | 5 3/4" | polished, with antiallergical coating | 26 g |
| 5-117-6 | 145 | 5 3/4" | nickel-plated, strong PVC insulated | 31 g |
| 5-117 VDE | 145 | 5 3/4" | with VDE insulation, 1000V | 39 g |
| 5-117-9 | 145 | 5 3/4" | teflon-coated | 29 g |



| | | | | |
|--|-----|--------|--|------|
| Engineer's tweezers made from steel, straight, with narrow pointed tips, finely serrated | | | | |
| 5-121 | 120 | 4 3/4" | nickel-plated | 14 g |
| 5-121-1 | 120 | 4 3/4" | polished, with antiallergical coating | 14 g |
| 5-121-6 | 120 | 4 3/4" | nickel-plated, strong PVC-insulated | 17 g |
| 5-121-9 | 120 | 4 3/4" | teflon-coated | 13 g |
| 5-122 | 155 | 6 1/8" | nickel-plated | 24 g |



| | | | | |
|---|-----|--------|--|------|
| Crossed tweezers (self-locking tweezers) made from steel, jaws 5 mm wide, finely serrated | | | | |
| 5-155 | 160 | 6 1/4" | polished-nickel-plated | 35 g |
| 5-155-1 | 160 | 6 1/4" | polished, with antiallergical coating | 36 g |



| | | | | |
|---|-----|--------|------------------------|------|
| Crossed soldering tweezers (self-locking tweezers) made from steel, with bent tips and gripping well hand guard | | | | |
| 5-156 | 160 | 6 1/4" | polished-nickel-plated | 29 g |

