



F-KL-6200 Palm OTDR

Product Summarizations:

F-KL-6200 palm OTDR is the newest instrument designed for testing FTTx network. It's mainly used to measure the physical characteristics of optical fiber under test, such as the length, the transmission loss and the splice loss etc.. It can also locate the faults or breaks of optical fiber. It's widely applied in the manufacture, construction and maintenance in optical fiber communication system.



F-KL-6200 palm OTDR is novel and beautiful in appearance.

F-KL-6200 offers three wavelengths and VLF in one handheld unit, especially for testing passive optical network (PON) in FTTx. In addition.

Mainly features:

- ◆ handheld、 lightweight and convenience for carrying
- ◆ Advanced anti-reflective TFT LCD, visible clearly in field
- ◆ 1.6m extra-short event dead zone
- ◆ 0.25m high resolution, 65535 sampling points
- ◆ Fast auto measurement, one-button operating
- ◆ Double USB interfaces, supporting USB stick and direct cable

download to PC via ActiveSync

- ◆ Supporting Bellcore GR196 file format in writing or reading
- ◆ Indicating remaining capacity of battery and warning if the voltage of battery is low.
- ◆ WinCE operation system, double operating interface of Chinese and



English

◆ Built-in lithium battery with high capacity for over 10 hours of operating life

◆ Visible fault locating (VFL)

◆ Universal FC/PC,FC/SC,FC/ST connector type, it's convenient for surface cleaning

◆ Unique function of updating system on-line, returning to factory is unnecessary

◆ **Extra-short Event Dead Zone**

F-KL-6200 palm OTDR has extra-short event dead zone, which is suitable for testing short optical fiber and pigtail optical fiber.

◆ **high-speed auto measurement**

The function of auto measurement of F-KL-6200 palm OTDR makes it unnecessary to operator to know about the further details of operating. Simply connect the fiber, press [Start],then the result is displayed in a few seconds, you can view the trace and event table.

◆ **High-speed auto analyzation**

F-KL-6200 can search and locate the events and faults in trace rapidly and precisely, and then lists all events in even table, so it's very useful to maintainers to improving efficiency and it's unnecessary to know about the relative background knowledge.

◆ **strong file management**

F-KL-6200 offers powerful function of file management. Besides saving, browsing or deleting files to or from USB stick and built-in memory, it can be connected to laser or inkjet printer based on PCL language, and the testing report can be printed rapidly and easily. In addition, F-KL-6200 can



communicate with PC using ActiveSync via USB cable, through which the files can be translated rapidly.

◆ **Convenient VFL**

The built-in 650nm visual fault location is ideal for easily identifying bad splice, bad connector, break or macro bend.

◆ **Application:**

F-KL-6200 Palm OTDR is mainly used to measure FTTx network, it provides a low cost solution for users. F-KL-6200 offers three measuring modes: manual mode (including real time mode and average mode), auto mode and dead zone mode.

Manual measurement mode: manual mode is suitable for skilled operator who is familiar with the instrument. In this measurement mode, to get more accurate results, real-time mode or average mode can be selected if necessary.

In real-time mode, the dynamic changes of fiber chain can be detected timely, it is very useful when you need to watch the effect and process of fiber being spliced or connected.

In average measurement mode, the noise in trace can be suppressed, and the SNR(signal noise ratio) is improved, therefore, the result is more accurate. In fact, the more average times is executed, the more noise in trace is suppressed, and the longer time is spent for signal processing. In practice, the average times should be set properly according to necessity.

Auto measurement mode: the optimized measurement conditions are set automatically, it's unnecessary to operator to know about the complicated background knowledge and the further details of operating. In this mode, the more accurate results can be gained when proper average times are set, but it



will increase the time of signal processing.

Dead zone mode: this mode is suitable for testing optical fiber with short distance and the optimized settings of distance range, pulse width and attenuator can be executed automatically. To get the best result, the terminal return loss should be guaranteed less than -40dB.

Specifications:

MODULE	3528	5626	35428
wavelength	1310nm/1550nm ±20nm	1550nm/1625nm ±20nm	1310nm/1550nm/1490nm ±20nm
Applicable Fiber	Single-mode		
Dynamic Range ¹	28/26dB	26/24dB	28/26/24dB
Distance Measurement Accuracy	±(1m + sample space + 0.003% * measurement distance)		
Event Dead Zone ²	≤1.6m		
Sampling Resolution	0.25, 0.5, 1, 2, 4, 8, 16m		
Distance Range	4, 8, 16, 32, 64, 128, 256km		
Pulse width	10, 30, 80, 160, 320, 640, 1280, 5120, 10240ns		
Loss threshold	0.01dB		
Sampling points	65534		
Linearity	0.05dB/dB		
Memory capacity	≥800 Traces		
IOR setting	1.00000~2.00000		
Display	Color LCD (touch screen)		



Interface	USB, Min-USB
VFL	650nm±10nm, 2mW(typical); CW/1Hz
Language	English
Optical Connector	FC/UPC (universal connector)
Power Supply	DC:15V~20V(3A), (AC adapter 100~240V,50/60Hz,1.5A),Built-in Lithium battery: 4400mAh,7.4V,operating time≥10 hours ³
Dimensions	210mm*100mm*60mm
Weight	about 1kg

Note1: pulse width 10240ns, average times≥300, SNR=1, 23°C±2°C;

Note2: Pulse width:10 ns, terminal reflection loss: ≥40dB, typical;

Note3: Low brightness, exclude measuring.

◆ Ordering information

Main frame: F-KL-6200 OTDR

Standard accessories:

NO.	Name	quantity
1	Power line	1
2	AC/DC adapter	1
3	Trace analyzing software、 User manual (CD)	1
4	Hard Carrying case	1

Note: For the necessity of improvement, the material contained in this document is subject to change without notice.