



Manual Date : 2017.05.25

Installation Manual

Q-ROI2 RGB Android Navigation Model : QROI2-RGB OCTA CORE

Specification

INDEX	CONTENS		
OS	Android 5.1.1 (Lollipop)		
СРՍ	Nexell S5P6818 (Cortex-A53 Octa-Core CPU up to 1.6GHz)		
Memory	DDR3 2GB up to 800MHz		
Internal Storage	8GB/16GB eMMC 5.1		
Display	OEM LCD / RGB / HDMI / CVBS		
Resolution	800 x 480		
SD CARD	Micro SD Slot Support (up to 64GB)		
GPS	UBLOX-8 (GPS + GLONASS)		
USB	2.0 High speed x 5 (USB Host x4, OTG x1)		
Touch	Resistive & Capacitive & UART Touch		
Video Input	CVBS x 1		
Map voice exclusive Speaker	3Watts/8ohm, 1 way mono		
Audio Output	Stereo Output x 1 (for Car Audio)		
Language	Multi-Language		
Power	DC 9V ~ 18V		
Operating Temperature	-10°C ~ 70°C		
Storage Temperature	-20°C ~ 80°C		

Product Exterior

TITUN

(118)

Components

Power * 1ea	Multi * 1ea	B/T board * 1ea	B/T Cable * 1ea
(HPOWER0137)	(HARETC0208)	(QCPASS0481)	(HARETC0209)
R touch cable * 1ea	RGB Out * 1ea	GPS Antenna * 1ea	Microphone cable * 1ea
HTOUCH0022	(HRGBCA0025)	(GPSANT0014)	(MICPHO0002)
HDMI cable * 1ea	USB cable * 1ea	Speaker * 1ea	BUTTON * 1ea
(HARETC0067)	(HARETC0111)	(SPEAKER009)	(HARETC0001)
Capts-ex-vi (140715) C touchstopsert@ear-so (Option)	lutions:confable * 1ea (HTOUCH0036)	WIFI dongle * 1ea (ETCETC0110) (Option) ^{www.c}	ar-solutions.com



* ON : DOWN / OFF : UP



•High resolution monitor with resistive touch panel



•Low resolution monitor with resistive touch panel



- •High resolution monitor with Uart capacitive touch panel
- •High resolution monitor with **QDIS** capacitive touch panel



 High resolution monitor with QDIS W222 capacitive touch panel

Installation



Setting



- * How to update the product
 - Copy and paste "update file" to USB stick driver.
 Once USB driver is inserted to USB port of Qroi, the popup window will be created for the update.
 Remove the USB driver after the completion.