

Installation Manual Q-ROI AUDI Q7 / A4

Warning / Precautions!



 Do not modify, dismantle or unintended operation this system outside Q-roi After Sales.
 Damage occurred by unintended operation may cause Q-roi After Sales service void.




- Always wear seatbelt. When the vehicle is suddenly stop can cause injury.
- **Warning** Remove dust, oil, and waste on the display.
 - Incidental damages (including, without limitation, consequential damages due to the use of this unit and the dead loss of business profit, changes, loss of memory contents, etc) will not be taken responsibility.
 - Any function that requires your prolonged attention should only be performed after coming to a complete stop. Always stop the vehicle in a safe location before performing these functions. Failure to do so may result in an accident.
 - The engine is off while the system operates for long time, battery may be discharged.
 - This product is not a substitute for your personal judgment. Any route suggested by this navigation system may never supersede any local traffic regulation. Do not follow route suggestions if the navigation system instructs you to perform an unsafe or illegal maneuver.

1. General Spec

OS	Android 4.2.2 (Jelly Bean)	
CPU	Telechips TCC8930 (1GHz Cortex A9 DualCore)	
Display	OEM LCD	
Internal Memory	DDR3 1GB RAM + 8GB eMMC	
External Memory	SDHC Slot Support (up to 64GB)	
Function	A/V Input x 3, Rear Cam Input x 1, CAN(Controller Area Network) x 2, Mic x 1, External Speaker x 1 (mono), External Audio Out x 1(Car Aux),	
Output	LVDS (thru Video Interface), RGB (thru Sub-Board)	
Touch Type	Resistive Touch	
GPS	SiRF	
Resolution	800*480	
USB	USB 2.0 x 5 (USB x 4, OTG USB x 1)	
Input Voltage	12V	
Temperature	operating 0 C to 60 C	
	Storage -20 C to 60 C	
Languages	multi-languages	

2. System Diagram



3. Components





(QCPASS0701)

PNL sub-board * 1ea (QCPASS0700)

SD Extension Cable * 1ea (HARETC0080)











Power cable 16P * 1ea (HPOWER0103)



JACK BY JACK cable * 1ea (HPOWER0102)



TOUCH cable * 1ea (HTOUCH0007)



GPS Antenna * 1ea (GPSANT0009)



MODE switch cable* 1ea (HARETC0001)



Multi cable * 1ea (HARETC0068)



Speaker * 1ea (SPEAKE0007)



AV/BT Cable * 1ea (HAVCAB0020)



Microphone cable * 1ea (MICPHO0001)




REAR CAMERA cable * 1ea (HARETC0002)

4. OEM Buttons (Q7)

*** Steering wheel**



*** MMI**




4. OEM Buttons (A4)

*** Steering wheel**



Long press : Q-ROI Screen Short press : OEM Screen

*** MMI**



5. Cautions before installation

- Ignition key should be taken off before starting installation, interface power connection must be the last step in installation.
- Power cable should be separated when connecting interface.
- Should be no any electronic devices or magnetic pole around installation place.
- All steps of installation should be done by well-trained specialist.
- Dismantling without manufacturer's permission can not be guaranteed, (No permission to break attached label on the board.)
- Kindly check all parts are in the box, when receiving the product, if anything missing, inform to the supplier or manufacturer.
- Install GPS away from electromagnetic devices such as black boxes, Hi-Pass and etc.
- Advisable to Install GPS at the edge of dash board or a front window or a rear window.
- Install GPS antenna mounted on window or roof facing to Sky.

6.1 Dip Switch Setting(MAIN BOARD)



PIN	Function	Dip \$/W
1,2,3	No use (OFF)	
4	Bluetooth Pop-up function	OFF : Bluetooth Pop-up use ON : Bluetooth Pop-up no use
5	Car model	5-ON, 6-OFF : Q7
6		5-OFF, 6-OFF : A4
7	Rear view camera	OFF : OEM RVC ON : External RVC
8	No use (OFF)	

**** PNL SUB-BOARD**



*** DSH SUB-BOARD**




PIN	Function	Dip \$/W
1, 2	Car model	1-OFF, 2-OFF : Q7 1-OFF, 2-OFF : A4
3,4	No use (OFF)	

PIN	Function	Dip S/W
1, 2	Car model	1-OFF, 2-OFF : Q7 1-ON, 2ON : A4
3,4	No use (OFF)	


^{**} Please make sure to disconnect the power cable of the interface and reconnect the power cable again to apply the dip switch setting whenever changing DIP switch. Otherwise, DIP switch setting will not be applied.
** www.car-solutions.com

6.2 Setting Factory Menu



- **※** APPS→FACTORY SETTING
- 1) Put Password and change program upgrade and set-up of external device. (Only Installers are authorized)
 - * Please contact the manufacturer to get Password.


6.2 Setting Factory Menu



- ① CAR MODEL: NO use
- ② DVD TYPE: Only for DVD connected to A/V

(Connect IR-AV1 to DVD to use DVD as touch Screen)

- ③ CMMB SELECT: Select DTV model (Only Chinese)
- **4** SETTING
 - GEAR CHECK TYPE: Detecting rear camera via either CAN or Rear Lamp.
 - REAR CAM : Put "On" External rear camera
 Put "Off" OEM Camera
 - SAFE MODE: Either Enable or Unable to watch Video while driving
 - MODE SWITCH: NO use
- (5) SAVE & EXIT: Save and Reboot



6.4 Power cable connection

