www.car-solutions.com



Operation manual QROIX Android system

support@car-solutions.com

car-solutions.com

Warning / Precautions!



Installation must be done at designated QROI A/S center. Do not dismantle, modify and install the product in the unauthorized places. In case of product Narning failure while installing the product in the unauthorized places warranty will be void



- Always wear a seatbelt. In case of a sudden stop, it may cause a passenger harm
- Narning Remove dust, oil, and waste on the display.
 - Manufacturer does not take a responsibility of Incidental damages that occurs whether or not passengers use its product.
 - Drivers must not use/control the product while driving. Park the car in a safe place in the first place before using it.
 - Do not use the product for a long time while engine is turned off. The car battery might go flat.
 - A map guided on the screen might not be in concordance with the actual road condition. In a such condition, follow the actual traffic situation.

1. Features

- Android 8.1 (OREO)
- •Powerful RAM and Internal Storage spec (RAM 4GB LPDDR3 & 32GB eMMC)
- Powerful CPU (ARM Cortex-A72 + Cortex-A53@2.0GHz (<u>HEXA CORE</u>) ARM Mali-T860 (<u>QUAD CORE</u>))
- Allows installing and updating various application via Android PlayStore
- Provides High quality video display (720P, simultaneous Video Output of LVDS

and HDMI)

- •Multiple ways to store data and communication ports (3 * USB, 1*Micro SD slot)
- •Supports AUX OUT by Bluetooth and FMTX
- •Access to the Internet & Data via WiFi and 4G Data via Dongle

(Dongle Option)

Program & FW update by USB Thumb memory stick

2. Specification

| CATEGORY | | SPECIFICATION | | |
|-----------------------|---------------------|--|--|--|
| OS Version | | 8.1 (OREO) | | |
| CPU | | ARM Cortex-A72 + <u>Cortex-A53@2.0GHz</u> (HEXA CORE) ARM Mali-T860 (QUAD CORE) - for GPU | | |
| | RAM | 4GB LPDDR3 | | |
| Memory | INTERNAL STORAGE | 32 GB eMMC | | |
| | EXTERNAL STORAGE | microSD slot (MAX 128GB) | | |
| | WI-FI | 802.11 a/b/g/n/ac (2.4 GHz / 5 GHz) Internally on board with Antenna | | |
| Network | BLUETOOTH | 4.0 (Internally on board with Antenna) | | |
| | MODEM | LTE + UMTS + GSM (CONNECT TYPE : External USB Dongle type): Option | | |
| | GPS | GPS + GLONASS | | |
| Video | Ουτ | LVDS 5CH x 1 / HDMI x 1 | | |
| Video | IN | None | | |
| Audio | ОИТ | AUX + SPK + BT AUX + FM TX | | |
| | IN | MIC | | |
| USB PORT | | HOST x 3 (Internal 2.0 Port x 1 + 3.0 Port x 1 / Extension Cable Port x 1) OTG x 1 | | |
| TOUCH INPUT | | Resistive + Capacitive + UART | | |
| Language | | Mulit-Language | | |
| Power | | DC 9V ~ 18V | | |
| Operating Temperature | | -10°C ~ 70°C | | |
| Storage Temperature | | -20°C ~ 80°C | | |

3.1 Main page

※ When QROIX is turned on, the main page is displayed as below



1 Status bar

Dragging down the status bar to view the information in details

2 Main icons

QROIX provides four main icons on the first page.

GPS and Multimedia icons operate as shortcuts to run the certain apps. (Users can set up the shortcut apps.)

3 Apps

Display the list of Android application

④ Settings

Change the settings

<u>6</u> Menu Bar : When dragging up the bottom, the menu bar comes.

- ${f P}$: Display and delete the apps from the recent operating apps list
- A
 - : Go back to main page
- <u>с</u>.
 - : Go back to the previous page
 - 🛜 : Go to WiFi setting

support@car-solutions.com

3.2 Change shortcut icons



1. Click the app with long press to make the shortcut on the main page.



2. Select the place to put in between GPS and MULTIMEDIA.

3.3 Bottom Menu bar

※ Menu bar helps to use QROI in a easier way.



- •Once the button is pressed, the recent apps will be displayed as shown on the left
- Replay the application when the application is clicked
- Remove the application on the recent apps by dragging left or right
- (Home key): (While running application) Go back to Home page (Long press) play Google Now



3. (back button): move to the previous page

4. (1): Turn on/off or Volume up/down Q-ROI sound



 click the button to open the new window as shown on the left

- AUX : Volume up/down Aux sound when the sound is connected to Car aux
- Speaker : Volume up/down the sound from the supplied speaker. In case of "Off", the supplied speaker will not have sound and only car aux will work
- MUTE : mute on/off

support@car-solutions.com

car-solutions.com

3.3 Bottom Menu bar

※ Menu bar helps to use QROI in a easier way.





6. 🛜 : Going to WiFi setting directly



7. O : Going to Android setting directly



3.4. How to use PIP function

1. 🗂

Please tap this multi-key icon

2. Please select and hold the app which you want to make PIP.



3. On the left side, the message shows that 'Drag here to use split screen'.



3.4. How to use PIP function

4. Please drag the app to the left side.



5. Then PIP screen will be operated without any problems.



4.1 QROI SETTINGS

Device Device

Device Settings

Settings





*Please tap Device Setting on App list.

*The Passwords are 0603.

1

0

*Can check AP and FW versions.

*Can do FW Update with plugging USB memory stick

*AP Update is automatically activated by plugging USB memory stick.

*Can set up FMTX



4.1 QROI SETTINGS

Device

Device Settings



4.1 QROI SETTINGS



4

Device Settings

| | 4 | | |
|-------------------------------|-----------------------------|-------------------|------------------|
| VERSION INFO | COOLING FAN MODE | | |
| AP : 005_200618_CS | - FAN MODE : AUTO CONTROL | | (5) |
| FW : Q.20.06.12 FW UPDATE | - CURRENT TEMP (°C) : 58.33 | | |
| AUDIO | DISPLAY | | |
| - FMTX FREQ : 1760 (88000 hz) | - LVDS Timing Controller | LVDS CONTROL | |
| PRESET > | | | |
| - Speaker BOOST : DISABLE | LINKED INTERFACE | | |
| SELECT | - QDIS | SELECT SAVE>RESET | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

*Cooling Fan Mode

: Please tap Mode select.



4.1 QROI SETTINGS



Device Settings

| VERSION INFO AP : 005_200618_CS FW : Q.20.06.12 FW UPDATE | COOLING FAN MODE - FAN MODE : AUTO CONTROL - CURRENT TEMP (°C) : 58.33 SELECT | ſ | |
|---|--|-------------------|----------|
| AUDIO | DISPLAY | | |
| - FMTX FREQ : 1760 (88000 hz) | - LVDS Timing Controller | LVDS CONTROL | |
| PRESET > | | | |
| - Speaker BOOST : DISABLE | LINKED INTERFACE | | <i>y</i> |
| SELECT | - QDIS | SELECT SAVE>RESET | |
| | | | |
| | | 5 | |
| | | | |

5 *Interface Setting: Select Interface Touch Protocol

| VERSION INFO | COOLING FAN MODE | | (|
|-------------------------------|---------------------------------------|-------------------|-----------------------|
| AP : 005_200618_CS | - FAN MODE : AUTO CONTROL | | (\leftrightarrow) |
| FW : Q.20.06.12 FW UPDATE | - CURRENT TEMP (°C) : 58.33 SELECT | | \bigcirc |
| AUDIO | DISPLAY | | |
| - FMTX FREQ : 1760 (88000 hz) | - LVDS Timing Controller | LVDS CONTROL | |
| PRESET > | | | |
| - Speaker BOOST : DISABLE | LINKED INTERFACE | | |
| SELECT | - QDIS | SELECT SAVE>RESET | |
| | | \ ") | |
| | | | 5 |
| | | | |

After selection, please tap Save \rightarrow RESET button, in order to save the chosen Interface protocol.

4.1 QROI SETTINGS



Device Settings

Device Settings



⁶*SPK BOOST: When Tap it, there are two options.

| VERSION INFO AP : 005_200618_CS FW : Q.20.06.12 FW UPDATE | COOLING FAN MODE - FAN MODE : AUTO CONTROL - CURRENT TEMP (°C) : 58.33 SELECT | (f) |
|---|--|--------------|
| AUDIO - FMTX FREQ : 1760 (83) Select | RESOLUTION SECTING | L/DS CONTROL |
| - Speaker BOOST : DISA | | |
| SPK B | OOST ENABLE | T SAVE>RESET |
| | | |

When SPK BOOST Enable is selected, Speaker volume Gain will be increased.

4.2 Touch Calibration



App list ► Touch Calibration

Touch Calibration



Touch Calibration.



Calibration is Complete.

•Press each target position by a finger.

•Completed.

support@car-solutions.com

Press back to quit.

4.4 System Info





*Can check the Android Version, Build Number and AP Version, as well as Released date

4.5 System Reset





5. HOW TO UPGRDE PROGRAMS

5.1 How to upgrade FW

*How to do FW Update.

- 1. Please copy and paste FW.QVL on USB memory stick root.
- 2. Please connect the USB memory stick to QROIX USB port. (Please don't connect it to OPTION port.)



- 3. Please go to Device settings.
- 4. Then please click FW UPDATE button on the menu.

| VERSION INFO | COOLING FAN MODE | NG FAN MODE | | |
|-------------------------------|---------------------------------------|-------------|------------|-----------------------|
| AP : 005_200618_CS | - FAN MODE : AUTO CONTROL | ONTROL | | (\leftrightarrow) |
| FW : Q.20.06.12 FW UPDATE | - CURRENT TEMP (°C) : 58.33 SELECT | | | \bigcirc |
| AUDIO | DISPLAY | | |) |
| - FMTX FREQ : 1760 (88000 hz) | - LVDS Timing Controller | LVD | S CONTROL | |
| PRESET > | | | | |
| - Speaker BOOST : DISABLE | LINKED INTERFACE | | |) |
| SELECT | - QDIS | SELECT | SAVE>RESET | |
| | | | | |
| | | | | |
| | | | | |

5. The pop up screen comes. Then please tap 'install now'.



6. The progress bar comes. After finishing the upgrade, QROIX reboots itself.

5. HOW TO UPGRDE PROGRAMS

5.1 How to upgrade APP program

*How to do APP Update.

- 1. Please copy and paste update.zip file on USB memory stick root.
- 2. Then please insert it to QROIX USB port. (Please don't use OPTION Port.
- 3. After that, please turn on QROIX again.
- 4. Automatically, update process is activated.